

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.04.2020 Version number 4 Revision: 03.04.2020

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE
- · Article number: L6.1.K1
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: LUSID TECHNOLOGIES 4725 S CAMP KEARNS ROAD KEARNS, UT 84118 USA www.lusidtechnologies.com
- · Further information obtainable from: Product safety department
- · Emergency telephone number:

Emergency US - 1-800-535-5053 Outside US - +1-352-323-3500 InfoTrac Contract 89244

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

(Contd. on page 2)

Printing date 03.04.2020 Version number 4 Revision: 03.04.2020

Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

ethylbenzene methanol

· Hazard statements

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled. H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate. May produce an allergic reaction.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions

Dangerous components:		
	4-chloro-alpha,alpha,alpha-trifluorotoluene ♦ Flam. Liq. 3, H226; ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	25-50%
	n-butyl acetate ⑤ Flam. Liq. 3, H226; ① STOT SE 3, H336	10-25%
L	xylene •• Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%

Printing date 03.04.2020 Version number 4 Revision: 03.04.2020

Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE

	(Con	td. of page 2
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225; UEye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 RTECS: DA 0700000 Reg.nr.: 01-2119489370-35	ethylbenzene ♦ Flam. Liq. 2, H225; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ↑ Acute Tox. 4, H332	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 RTECS: ZE 2100000 Reg.nr.: 01-2119488216-32	xylene Tam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	≤2.5%
CAS: 41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate ♦ Skin Sens. 1, H317	≤2.5%
CAS: 123-54-6 EINECS: 204-634-0 Index number: 606-029-00-0 RTECS: SA 1925000	pentane-2,4-dione Tox. 3, H311; Acute Tox. 3, H311; Acute Tox. 4, H302	≤2.5%
EINECS: 200-659-6	methanol ♠ Flam. Liq. 2, H225; ♦ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ♦ STOT SE 1, H370	≤2.5%

4 First aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

Printing date 03.04.2020 Version number 4 Revision: 03.04.2020

Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE

(Contd. of page 3)

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)

Printing date 03.04.2020 Version number 4 Revision: 03.04.2020

Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE

(Contd. of page 4)

· Control parameters
· Ingredients with limit values that require monitoring at the workplace:
123-86-4 n-butyl acetate
IOELV Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm
1330-20-7 xylene
IOELV Short-term value: 50 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin
67-64-1 acetone
IOELV Long-term value: 1210 mg/m³, 500 ppm
100-41-4 ethylbenzene
IOELV Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin
1330-20-7 xylene
IOELV Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin
67-56-1 methanol
IOELV Long-term value: 260 mg/m³, 200 ppm Skin

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Printing date 03.04.2020 Version number 4 Revision: 03.04.2020

Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Ph	vsical	and o	chemi	cal	pro	perties
· • · · · · ·	, Crou	and (91101111	our	$\rho_1 \circ$	

· Information	on basic r	hyeical and	chomical	nronortios
· miormation	on basic L	mvsicai anu	Crieniicai	broberties

· General Information

· Appearance:

Form:
Colour:
Whitish
Odour:
Characteristic
Not determined.

PH-value:
Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 55.8-56.6 °C

· Flash point: <-18 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 465 °C

· **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 7.5 Vol %

· Vapour pressure at 20 °C: 10.7 hPa

Density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 1.1296 g/cm³
 Not determined.
 Not determined.
 Not determined.

· Solubility in / Miscibility with

water: Fully miscible.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

(Contd. on page 7)

Printing date 03.04.2020 Version number 4 Revision: 03.04.2020

Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE

(Contd. of page 6)

· Solvent content:

 Organic solvents:
 38.1-41.9 %

 VOC (EC)
 70.13-73.99 %

Solids content: 24.6 %

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

Printing date 03.04.2020 Revision: 03.04.2020 Version number 4

Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE

(Contd. of page 7)

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

Transport information	
UN-Number ADR, IMDG, IATA	UN1263
UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml
Transport category	Maximum net quantity per outer packaging: 500 ml 2

Printing date 03.04.2020 Version number 4 Revision: 03.04.2020

Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE

Tunnel restriction code
 IMDG
 Limited quantities (LQ)
 Excepted quantities (EQ)
 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 UN "Model Regulation":

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Roberts
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.04.2020 Version number 4 Revision: 03.04.2020

Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE

(Contd. of page 9)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity - dermal - Category 3 Acute Tox. 4: Acute toxicity - dermal - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1