

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018 Reviewed on 12/05/2017

1 Identification

· Product identifier

· Trade name: SHS17 BRIGHT RED MIXING TINT

- Article number: SHS17

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Lusid Technologies 5195 West 4700 South KEARNS, UT 84118 USA

www.lusid.biz

- · Information department: Product safety department
- Emergency telephone number:

24 Hrs Emergency Contact:

INFOTRAC 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: SHS17 BRIGHT RED MIXING TINT

Hazard pictograms







GHS07

- · Signal word Warning
- Hazard-determining components of labeling:

n-butyl acetate

· Hazard statements

Flammable liquid and vapor.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 4)



Health = 1Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 3

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: SHS17 BRIGHT RED MIXING TINT

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|-------------------------|-----------------|--------|
| 123-86-4 | n-butyl acetate | 25-50% |
| 110-43-0 | heptan-2-one | 10-25% |
| 1330-20-7 | xylene | ≤2.5% |
| 100-41-4 | ethylbenzene | ≤2.5% |

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

123-86-4 n-butyl acetate

5 ppm

(Contd. on page 4)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: SHS17 BRIGHT RED MIXING TINT

| | | (Contd. of page |
|-----------|------------------|-----------------|
| 110-43-0 | heptan-2-one | 150 ppn |
| 1330-20-7 | xylene | 130 ppn |
| 100-41-4 | ethylbenzene | 33 ppm |
| 122-99-6 | 2-Phenoxyethanol | 1.5 ppm |
| · PAC-2: | | |
| 123-86-4 | n-butyl acetate | 200 ppm |
| 110-43-0 | heptan-2-one | 670 ppm |
| 1330-20-7 | xylene | 920* ppm |
| 100-41-4 | ethylbenzene | 1100* ppn |
| 122-99-6 | 2-Phenoxyethanol | 16 ppm |
| · PAC-3: | | |
| 123-86-4 | n-butyl acetate | 3000* ppn |
| 110-43-0 | heptan-2-one | 4000* ppn |
| 1330-20-7 | xylene | 2500* ppn |
| 100-41-4 | ethylbenzene | 1800* ppn |
| 122-99-6 | 2-Phenoxyethanol | 97 ppm |

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- Control parameters

| · Con | troi parameters |
|-------|---|
| · Con | ponents with limit values that require monitoring at the workplace: |
| 123- | 86-4 n-butyl acetate |
| PEL | Long-term value: 710 mg/m³, 150 ppm |
| REL | Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm |
| TLV | Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm |
| 110- | 43-0 heptan-2-one |
| PEL | Long-term value: 465 mg/m³, 100 ppm |
| REL | Long-term value: 465 mg/m³, 100 ppm |

(Contd. on page 5)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: SHS17 BRIGHT RED MIXING TINT

(Contd. of page 4) TLV Long-term value: 233 mg/m³, 50 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m3, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 651 mg/m3, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI · Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids 100-41-4 ethylbenzene BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: SHS17 BRIGHT RED MIXING TINT

· Penetration time of glove material

(Contd. of page 5)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



· Viscosity: Dynamic:

Kinematic:

Tightly sealed goggles

· Partition coefficient (n-octanol/water): Not determined.

| Information on basic physical and General Information | cnemical properties |
|---|--|
| · Appearance: | |
| Form: | Liquid |
| Color: | Red |
| · Odor: | Characteristic |
| · Odor threshold: | Not determined. |
| · pH-value: | Not determined (pH N/A in solvent coatings) |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 124 ℃ (255.2 °F) |
| · Flash point: | 27 °C (80.6 °F) |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | 370 ℃ (698 ℉) |
| Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive a vapor mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1 Vol % |
| Upper: | 7.5 Vol % |
| · Vapor pressure at 20 ℃ (68 ℉): | 10.7 hPa (8 mm Hg) |
| · Density at 20 ℃ (68 ℉): | 1.0397 g/cm³ (8.6763 lbs/gal) |
| Relative density | Not determined. |
| Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| Water: | Not miscible or difficult to mix. |

Not determined.

Not determined.

(Contd. on page 7)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: SHS17 BRIGHT RED MIXING TINT

(Contd. of page 6)

Solvent content:
Organic solvents:
VOC content:

37.40 % 392.9 g/l / 3.28 lb/gal

Solids content: 62.2 %

· Other information No further relevant information available.

37.4 %

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

| · IARC (Inte | ernational Agency for Research on Cancer) | |
|--------------|---|----|
| 1330-20-7 | xylene | 3 |
| 100-41-4 | ethylbenzene | 2B |
| · NTP (Natio | onal Toxicology Program) | |
| None of the | e ingredients is listed. | |
| · OSHA-Ca | (Occupational Safety & Health Administration) | |
| None of the | e ingredients is listed. | |

12 Ecological information

- **Toxicity**
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

(Contd. on page 8)

(Contd. of page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: SHS17 BRIGHT RED MIXING TINT

· Additional ecological information:

· Additional ecological information. · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| UN-Number DOT, IMDG, IATA | UN1263 | |
|---|----------------------------|--|
| UN proper shipping name DOT | Paint | |
| IMDG, IATA | PAINT | |
| Transport hazard class(es) | | |
| DOT | | |
| FLAMMARE LUCID | | |
| Class Label | 3 Flammable liquids 3 | |
| IMDG, IATA | | |
| | | |
| Class | 3 Flammable liquids | |
| Label | 3 | |
| Packing group DOT, IMDG, IATA | III | |
| Environmental hazards: Marine pollutant: | No | |
| Special precautions for user | Warning: Flammable liquids | |

(Contd. of page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: SHS17 BRIGHT RED MIXING TINT

· Danger code (Kemler): 30 · EMS Number: F-E,S-E · Stowage Category A

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

· Quantity limitations On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

100-41-4 ethylbenzene

122-99-6 2-Phenoxyethanol

TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

Chemicals known to cause cancer:

100-41-4 ethylbenzene

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

 1330-20-7
 xylene
 I

 100-41-4
 ethylbenzene
 D

TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene A4

(Contd. on page 10)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: SHS17 BRIGHT RED MIXING TINT

(Contd. of page 9)

100-41-4 ethylbenzene

A3

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

n-butyl acetate

Hazard statements

Flammable liquid and vapor.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Product Safety Dept.
- Date of preparation / last revision 08/06/2018 / 2
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 11)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: SHS17 BRIGHT RED MIXING TINT

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

(Contd. of page 10)