

Page 1/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

### 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER
- · Article number: P6.3.K1
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
  Lusid Technologies
  4725 S Camp Kearns Road
  Kearns, UT 84118
  USA

www.lusidtechnologies.com

- · Further information obtainable from: Product safety department
- · Emergency telephone number:

Emergency US - 1-800-535-5053 Outside US - +1-352-323-3500 InfoTrac Contract 89244

#### 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 1)

#### · Hazard pictograms







GHS02 GHS07

#### Signal word Danger

#### · Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

Stoddard solvent

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Contains 2-butanone oxime. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Restricted to professional users.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

## 3 Composition/information on ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene EINECS: 202-681-1 🚸 Flam. Liq. 3, H226; 🕔 Skin Irrit. 2, H315; Eye Irrit. 2,

H319 Reg.nr.: 01-2119857280-40

(Contd. on page 3)

25-50%

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

		td. of page
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate     Flam. Liq. 3, H226	10-25%
CAS: 107-87-9 EINECS: 203-528-1 Index number: 606-007-00-0 RTECS: SA 7875000	pentan-2-one  Flam. Liq. 2, H225; Acute Tox. 4, H302	2.5-10%
CAS: 110-43-0 EINECS: 203-767-1 Index number: 606-024-00-3 Reg.nr.: 01-2119902391-49-0000	heptan-2-one  Flam. Liq. 3, H226;  Acute Tox. 4, H302; Acute Tox. 4, H332	2.5-10%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom.  The property of the property of the property of the period	2.5-10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	titanium dioxide © Carc. 2, H351	2.5-10%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate)  Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≤2.5%
CAS: 95-63-6 EINECS: 202-436-9 Index number: 601-043-00-3	1,2,4-trimethylbenzene  Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≤2.5%
CAS: 8052-41-3 EINECS: 232-489-3 Index number: 649-345-00-4 RTECS: WJ 8925000	Stoddard solvent  Stoddard solvent  Flam. Liq. 3, H226; Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304	≤2.5%
CAS: 96-29-7 EINECS: 202-496-6 Index number: 616-014-00-0	2-butanone oxime <b>♦</b> Carc. 2, H351; <b>♦</b> Eye Dam. 1, H318; <b>♦</b> Acute Tox. 4, H312; Skin Sens. 1, H317	≤2.5%

## 4 First aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

FU

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 4)

### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

Ingredients wi	Ingredients with limit values that require monitoring at the workplace:		
108-65-6 2-methoxy-1-methylethyl acetate			
IOELV (EU)	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin		
VLEP (France)	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm risque de pénétration percutanée		
107-87-9 penta	n-2-one		
VLEP (France)	Long-term value: 705 mg/m³, 200 ppm		
110-43-0 hepta	nn-2-one		
IOELV (EU)	Short-term value: 475 mg/m³, 100 ppm Long-term value: 238 mg/m³, 50 ppm Skin		
VLEP (France)	Short-term value: 475 mg/m³, 100 ppm Long-term value: 238 mg/m³, 50 ppm risque de pénétration percutanée		
95-63-6 1,2,4-tı	rimethylbenzene		
IOELV (EU)	Long-term value: 100 mg/m³, 20 ppm		
VLEP (France)	Short-term value: 250 mg/m³, 50 ppm Long-term value: 100 mg/m³, 20 ppm		

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 6)

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 5)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Colour: According to product specification

Odour: Product specific
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

**Melting point/freezing point:** Undetermined. **Initial boiling point and boiling range:** 101.7 °C

· Flash point: 7 °C

Flammability (solid, gas): Not applicable.

· **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

**Lower:** 1.5 Vol % **Upper:** 10.8 Vol %

· Vapour pressure at 20 °C: 3.4 hPa

Density at 20 °C: 1.34 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Fully miscible.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

(Contd. on page 7)

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

		(Contd. of page 6
· Solvent content:		
Organic solvents:	37.0 %	
VOC (EC)	82.04 %	
Solids content:	51.7 %	
· Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:		
64742-95-	6 Solvent	naphtha (petroleum), light arom.	
Oral	LD50	>6,800 mg/kg (rat)	
Dermal	LD50	>3,400 mg/kg (rab)	
Inhalative	LC50/4 h	>10.2 mg/l (rat)	
7779-90-0	7779-90-0 trizinc bis(orthophosphate)		
Oral	LD50	>5,000 mg/kg (rat)	
95-63-6 1,	2,4-trimet	hylbenzene	
Oral	LD50	5,000 mg/kg (rat)	
64742-48-	9 Naphtha	(petroleum), hydrotreated heavy	
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>3,000 mg/kg (rab)	

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity

May cause genetic defects.

- · Carcinogenicity
- May cause cancer.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 7)

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Harmful to aquatic organisms

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

#### 14 Transport information

· UN-Number · ADR, IMDG, IATA	UN1263	
· UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT	

- · Transport hazard class(es)
- · ADR, IMDG, IATA



· Class 3 Flammable liquids. 3

· Label

(Contd. on page 9)

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

	(Contd. of page
Packing group	
ADR, IMDG, IATA	II .
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemle	er code): 33
EMS Number:	F-E,S-E
Stowage Category	В
Transport in bulk according to Anne	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E2
, ,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT, 3, II

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 28, 29
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

(Contd. on page 10)

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 9)

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

#### · Department issuing SDS: Environment protection department.

· Contact: Mr. Roberts

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Muta. 1B: Germ cell mutagenicity - Category 1B

(Contd. on page 11)

Page 11/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.11.2021 Version number 2 Revision: 11.11.2021

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 10)

Carc. 1B: Carcinogenicity – Category 1B
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3