

Printing date 01/14/2025

Reviewed on 01/14/2025

1 Identification · Product identifier Trade name: SHS56 COARSE STARFLAKE · Article number: SHS56 · Details of the supplier of the safety data sheet · Manufacturer/Supplier: NorthStar is a product of Lusid Technologies Inc 4725 S Camp Kearns Road Kearns, UT 84118 (801) 966-5300 info@lusidtechnologies.com · Information department: Product safety department · Emergency telephone number: 24 Hrs Emergency Contact: **INFOTRAC** 1-800-535-5053 2 Hazard(s) identification · Classification of the substance or mixture GHS02 Flame H226 Flammable liquid and vapor. Flammable Liquids 3 Substances and mixtures which, in contact with H261 In contact with water releases flammable water, emit flammable gases 2 gas. GHS08 Health hazard Germ Cell Mutagenicity 1B H340 May cause genetic defects. Carcinogenicity 1A H350 May cause cancer. GHS07 Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) - USA

Page 1/13

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: n-butvl acetate Solvent naphtha (petroleum), light arom. Naphtha (petroleum), hydrotreated heavy ethylbenzene · Hazard statements Flammable liquid and vapor. In contact with water releases flammable gas. May cause genetic defects. May cause cancer. May cause drowsiness or dizziness. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not allow contact with water. Handle under inert gas. Protect from moisture. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages. In case of fire: Use CO2, sand, extinguishing powder to extinguish. Store in a drv place. Store in a closed container. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: • NFPA ratings (scale 0 - 4) Health = 0Fire = 3Reactivity = 2

The substance demonstrates unusual reactivity with water.

(Contd. on page 3)

LISA

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)



· Other hazards

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

[•] Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

[.] Dangerous	components:	
	n-butyl acetate	25-50%
7429-90-5	aluminium	10-25%
	Naphtha (petroleum), hydrotreated heavy	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
1330-20-7	xylene	≤2.5%
100-41-4	ethylbenzene	≤2.5%
64-17-5	ethanol	≤2.5%
67-56-1	methanol	≤2.5%

4 First-aid measures

- [.] Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed* No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
 Suitable extinguishing agents: Extinguishing powder. Do not use water.
 CO2. Do not use water.
 Sand. Do not use water.
 Special powder for metal fires. Do not use water.
 CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
- Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- **Reference to other sections** See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

123-86-4	n-butyl acetate	5 ppm
	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
1330-20-7		130 ppm
	ethylbenzene	33 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
64-17-5	ethanol	1,800 ppm
67-56-1	methanol	530 ppm
7664-38-2	phosphoric acid	3 mg/m ³
122-99-6	2-phenoxyethanol	1.5 ppm
67-63-0	propan-2-ol	400 ppm
PAC-2:		
123-86-4	n-butyl acetate	200 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
64-17-5	ethanol	3300* ppm
67-56-1	methanol	2,100 ppm
7664-38-2	phosphoric acid	30 mg/m³
122-99-6	2-phenoxyethanol	16 ppm
67-63-0	propan-2-ol	2000* ppm
PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
		(Contd. on page

(Contd. of page 3)

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

	(Contd. of page 4)
108-65-6 2-methoxy-1-methylethyl acetate	5000* ppm
64-17-5 ethanol	15000* ppm
67-56-1 methanol	7200* ppm
7664-38-2 phosphoric acid	150 mg/m³
122-99-6 2-phenoxyethanol	97 ppm
67-63-0 propan-2-ol	12000** ppm

7 Handling and storage

· Handling:

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

[•] Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

123-	86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 150 ppm Long-term value: 50 ppm	
1330	-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, A4	
		(Contd. on page 6

[·] Control parameters

Components with limit values that require monitoring at the workplace:

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

	1-4 ethylbenzene	(Contd. of page
	Long-term value: 435 mg/m³, 100 ppm	
	Short-term value: 545 mg/m³, 125 ppm	
	Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm	
	OTO, BEI, A3	
	-5 ethanol	
	Long-term value: 1900 mg/m³, 1000 ppm	
	Long-term value: 1900 mg/m³, 1000 ppm	
	Short-term value: 1000 ppm A3	
	-1 methanol	
	Long-term value: 260 mg/m³, 200 ppm	
	Short-term value: 325 mg/m³, 250 ppm	
	Long-term value: 260 mg/m³, 200 ppm	
	Skin	
	Short-term value: 250 ppm	
	Long-term value: 200 ppm	
	Skin; BElc	
	dients with biological limit values:	
	20-7 xylene	
	1.5 g/g creatinine Medium: urine	
	Time: end of shift	
	Parameter: Methylhippuric acids	
100-4	1-4 ethylbenzene	
	0.15 g/g creatinine	
	Medium: urine	
	Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)	
	anameter. Sum of mandelic acid and phenyigiyoxylic acid (nonspecific)	
	15 mg/L	
	Medium: urine	
	Time: end of shift	
ŀ	Parameter: Methanol (background, nonspecific)	

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

(Contd. of page 6)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Light grey
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined (pH N/A in solvent coatings)
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)
Flash point:	27 °C (80.6 °F)
Flammability:	Flammable.
2	Contact with water liberates extremely flammable gases.
Auto igniting:	370 °C (698 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

		(Contd. of page
Upper:	7.5 Vol %	
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)	
Vapor pressure at 50 °C (122 °F):	55 hPa (41.3 mm Hg)	
Density at 20 °C (68 °F):	1.1217 g/cm³ (9.3606 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	47.0 %	
VOC content:	47.01 %	
	460.0 g/l / 3.84 lb/gal	
Solids content:	59.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions Contact with water releases flammable gases.
- **Conditions to avoid** No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	13,100 mg/kg (rat) >5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

· Primary irritant effect:

- on the skin: No irritant effect.
- · on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

(Contd. on page 9)

USA

(Contd. of page 8)

3

1

3

2B

Safety Data Sheet acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

The product can cause inheritable damage.

Carcinogenic categories

 IARC (International Agency for Research on C 	ancer)
--	--------

1330-20-7 xylene

100-41-4 ethylbenzene 64-17-5 ethanol

67-63-0 propan-2-ol

· NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

UN3148

(Contd. on page 10)

USA

Safety Data Sheet acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE			
	(Contd. of page 9)		
· UN proper shipping name · DOT · IMDG, IATA	Water-reactive liquid, n.o.s. (Aluminum powder) WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER)		
· Transport hazard class(es)			
·DOT			
DANGEROUS th			
· Class	4.3 Substances which, in contact with water, emit flammable gases		
·Label	4.3		

· IMDG, IATA



· Class	4.3 Substances which, in contact with water, emit flammable gases
[.] Label	4.3
· Packing group	
· DOT, IMĎG, IATA	11
· Environmental hazards:	Not applicable.

	, ,
 Special precautions for user 	Warning: Substances which, in contact with water, emit flammable gases
· Hazard identification number (Kemler code):	429
· EMS Number:	F-G,S-N
· Segregation groups	(SGG15) Powdered metals
Stowage Category	Ē
· Stowage Code	SW2 Clear of living quarters.

• Stowage Code • Handling Code • Segregation Code	SW2 Clear of living quarters. H1 Keep as dry as reasonably practicable SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained.
 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 5 L
· IMDG · Limited quantities (LQ)	500 ml

(Contd. on page 11) - USA

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

	(Contd. of page 10)
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 3148 WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER), 4.3, II

15 Regulatory information

	the same after set as the first and	
Section 31	ingredients is listed.	
	3 (Specific toxic chemical listings):	
7429-90-5	aluminium	
1330-20-7	xylene	
100-41-4	ethylbenzene	
67-56-1	methanol	
7664-38-2	phosphoric acid	
122-99-6	2-phenoxyethanol	
67-63-0	propan-2-ol	
TSCA (Tox	ic Substances Control Act):	
All compon	ents have the value ACTIVE.	
Hazardous	Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
67-56-1	methanol	
Propositio		
Chemicals	known to cause cancer:	
100-41-4 e	thylbenzene	
Chemicals	known to cause reproductive toxicity for females:	
None of the	ingredients is listed.	
Chemicals	known to cause reproductive toxicity for males:	
None of the	ingredients is listed.	
Chemicals	known to cause developmental toxicity:	
64-17-5 et	nanol	
67-56-1 m	ethanol	
Carcinoge	nic categories	
	ronmental Protection Agency)	
1330-20-7	xylene	
100-41-4	ethylbenzene	
TLV (Three	shold Limit Value)	
7429-90-5	aluminium	F

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

100-11-1	ethylbenzene	(Contd. of page
64-17-5		/
	propan-2-ol	
	(National Institute for Occupational Safety and Health)	
	e ingredients is listed.	
GHS label The produc Hazard pic	ct is classified and labeled according to the Globally Harmonized System (GF	HS).
GHS02	GHS07 GHS08	
Signal wo	rd Danger	
Hazard-de	etermining components of labeling:	
	phtha (petroleum), light arom.	
Naphtha (p	petroleum), hydrotreated heavy	
ethylbenze		
Hazard sta		
	e liquid and vapor. with water releases flammable gas.	
	e genetic defects.	
May cause		
	e drowsiness or dizziness.	
	nary statements	
	cial instructions before use.	
Do not han	ndle until all safety precautions have been read and understood.	
	/ from heat/sparks/open flames/hot surfaces No smoking.	
	w contact with water.	
	der inert gas. Protect from moisture.	
	nd container and receiving equipment.	
	sion-proof electrical/ventilating/lighting/equipment.	
	on-sparking tools.	
	autionary measures against static discharge. thing dust/fume/gas/mist/vapors/spray	
	utdoors or in a well-ventilated area. active gloves/protective clothing/eye protection/face protection.	
	or hair): Take off immediately all contaminated clothing. Rinse skin with wate	r/shower
	D: Remove person to fresh air and keep comfortable for breathing.	
	d or concerned: Get medical advice/attention.	
	on center/doctor if you feel unwell.	
	pose particles from skin. Immerse in cool water/wrap in wet bandages.	
	fire: Use CO2, sand, extinguishing powder to extinguish.	
	dry place. Store in a closed container.	
	well-ventilated place. Keep container tightly closed.	
	well-ventilated place. Keep cool.	
Store locke		
Dispose of	contents/container in accordance with local/regional/national/international re	gulations. (Contd. on page

Printing date 01/14/2025

· National regulations:

Reviewed on 01/14/2025

Trade name: SHS56 COARSE STARFLAKE

(Contd. of page 12)

· Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out. 16 Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Department issuing SDS: Environment protection department. · Contact: Product Safety Dept. Date of preparation / last revision 01/14/2025 / -· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Substances and mixtures which, in contact with water, emit flammable gases 2: Substances and mixtures which in contact with water emit flammable gases - Category 2 Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B Carcinogenicity 1A: Carcinogenicity - Category 1A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 USA