

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

1 Identification

- **Product identifier**
- **Trade name: 150B 150 SERIES BINDER**
- **Article number: 150B**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
NorthStar is a product of Lusid Technologies Inc
4725 S Camp Kearns Road
Kearns, UT 84118
(801) 966-5300
info@lusidtechnologies.com
- **Information department: Product safety department**
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B H340 May cause genetic defects.
Carcinogenicity 1B H350 May cause cancer.
Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2 H315 Causes skin irritation.
Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: 150B 150 SERIES BINDER

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated light
Stoddard solvent
Solvent naphtha (petroleum), light arom.
2-butanone oxime

- **Hazard statements**

Flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
May be fatal if swallowed and enters airways.

- **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
Specific treatment (see on this label).
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If exposed or concerned: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: 150B 150 SERIES BINDER

(Contd. of page 2)

- **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = *1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	25-50%
64742-49-0	Naphtha (petroleum), hydrotreated light	10-25%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%
8052-41-3	Stoddard solvent	≤2.5%
96-29-7	2-butanone oxime	≤2.5%
136-52-7	cobalt(II) 2-ethylhexanoate	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: 150B 150 SERIES BINDER

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

1330-20-7	xylene	130 ppm
8052-41-3	Stoddard solvent	300 mg/m ³
96-29-7	2-butanone oxime	30 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
122-99-6	2-phenoxyethanol	1.5 ppm
100-41-4	ethylbenzene	33 ppm
149-57-5	2-ethylhexanoic acid	15 mg/m ³

- **PAC-2:**

1330-20-7	xylene	920* ppm
8052-41-3	Stoddard solvent	1,800 mg/m ³
96-29-7	2-butanone oxime	56 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
122-99-6	2-phenoxyethanol	16 ppm
100-41-4	ethylbenzene	1100* ppm
149-57-5	2-ethylhexanoic acid	99 mg/m ³

- **PAC-3:**

1330-20-7	xylene	2500* ppm
8052-41-3	Stoddard solvent	29500** mg/m ³
96-29-7	2-butanone oxime	250 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
122-99-6	2-phenoxyethanol	97 ppm
100-41-4	ethylbenzene	1800* ppm
149-57-5	2-ethylhexanoic acid	590 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: 150B 150 SERIES BINDER

(Contd. of page 4)

Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

64742-49-0 Naphtha (petroleum), hydrotreated light

TLV	Long-term value: 100 ppm Skin, A3
-----	--------------------------------------

8052-41-3 Stoddard solvent

PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 100 ppm

96-29-7 2-butanone oxime

WEEL	Long-term value: 10 ppm DSEN
------	---------------------------------

136-52-7 cobalt(II) 2-ethylhexanoate

TLV	Long-term value: 0.02* mg/m ³ as Co, A3; *inhalable; DSEN; RSEN; BEI
-----	--

- **Ingredients with biological limit values:**

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: 150B 150 SERIES BINDER

(Contd. of page 5)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Light brown
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined (pH N/A in solvent coatings)

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	137-143 °C (278.6-289.4 °F)

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: 150B 150 SERIES BINDER

(Contd. of page 6)

· Flash point:	30 °C (86 °F)
· Flammability:	Flammable.
· Auto igniting:	500 °C (932 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7-8.2 hPa (5-6.2 mm Hg)
· Density at 20 °C (68 °F):	0.9809 g/cm ³ (8.1856 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	53.0 %
VOC content:	53.35 %
	519.8 g/l / 4.34 lb/gal
Solids content:	47.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: 150B 150 SERIES BINDER

(Contd. of page 7)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
136-52-7	cobalt(II) 2-ethylhexanoate	2B
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

USA

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025



Trade name: 150B 150 SERIES BINDER

(Contd. of page 8)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|----------------------------|
| UN-Number | UN1263 |
| DOT, IMDG, IATA | UN1263 |
| UN proper shipping name | Paint |
| DOT | PAINT |
| IMDG, IATA | PAINT |
| Transport hazard class(es) | |
| DOT | |
|  | |
| Class | 3 Flammable liquids |
| Label | 3 |
| | |
| IMDG, IATA | |
|  | |
| Class | 3 Flammable liquids |
| Label | 3 |
| Packing group | III |
| DOT, IMDG, IATA | III |
| Environmental hazards: | |
| Marine pollutant: | No |
| Special precautions for user | Warning: Flammable liquids |
| Hazard identification number (Kemler code): | 30 |
| EMS Number: | F-E, S-E |
| Stowage Category | A |
| Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: 150B 150 SERIES BINDER

(Contd. of page 9)

- **Transport/Additional information:**
- **DOT**
- **Quantity limitations**

	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1

	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
- **UN "Model Regulation":** UN 1263 PAINT, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
136-52-7	cobalt(II) 2-ethylhexanoate
112-34-5	2-(2-butoxyethoxy)ethanol
122-99-6	2-phenoxyethanol
100-41-4	ethylbenzene

- **TSCA (Toxic Substances Control Act):**

1330-20-7	xylene	ACTIVE
8052-41-3	Stoddard solvent	ACTIVE
96-29-7	2-butanone oxime	ACTIVE
136-52-7	cobalt(II) 2-ethylhexanoate	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
112-34-5	2-(2-butoxyethoxy)ethanol	ACTIVE
122-99-6	2-phenoxyethanol	ACTIVE
100-41-4	ethylbenzene	ACTIVE
149-57-5	2-ethylhexanoic acid	ACTIVE

- **Hazardous Air Pollutants**

1330-20-7	xylene
136-52-7	cobalt(II) 2-ethylhexanoate
100-41-4	ethylbenzene

- **Proposition 65**

- **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: 150B 150 SERIES BINDER

(Contd. of page 10)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated light
Stoddard solvent

Solvent naphtha (petroleum), light arom.

2-butanone oxime

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2025

Reviewed on 01/14/2025

Trade name: 150B 150 SERIES BINDER

(Contd. of page 11)

Do NOT induce vomiting.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF exposed or concerned: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**
 Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**
 Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 01/14/2025 / 6
- **Abbreviations and acronyms:**
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flammable Liquids 3: Flammable liquids – Category 3
 Skin Irritation 2: Skin corrosion/irritation – Category 2
 Sensitization - Skin 1: Skin sensitisation – Category 1
 Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B
 Carcinogenicity 1B: Carcinogenicity – Category 1B
 Aspiration Hazard 1: Aspiration hazard – Category 1
- *** Data compared to the previous version altered.**

USA