

Printing date 08/06/2018

Reviewed on 12/05/2017

Page 1/11

1 Identification

- · Product identifier
- · Trade name: SHS50 BRIGHT RED MIXING TINT
- · Article number: shs50
- · Details of the supplier of the safety data sheet

Manufacturer/Supplier: Lusid Technologies 5195 West 4700 South KEARNS, UT 84118 USA www.lusid.biz

 Information department: Product safety department
 Emergency telephone number: 24 Hrs Emergency Contact: INFOTRAC 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



H351 Suspected of causing cancer.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements


The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: SHS50 BRIGHT RED MIXING TINT



(Contd. on page 3)

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: SHS50 BRIGHT RED MIXING TINT

(Contd. of page 2)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangero	us components:	
123-86-4	n-butyl acetate	25-50%
	DPP Red C.I Pigment 254	10-25%
110-43-0	heptan-2-one	2.5-10%
100-41-4	ethylbenzene	<i>≤</i> 2.5%

4 First-aid measures

Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. • Environmental precautions: Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. Protective Action Criteria for Chemicals · PAC-1:

5 ppm

123-86-4 n-butyl acetate

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: SHS50 BRIGHT RED MIXING TINT

		(Contd. of page 3
	heptan-2-one	150 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
108-38-3	m-xylene	130 ppm
122-99-6	2-Phenoxyethanol	1.5 ppm
14808-60-7	Quartz (SiO2)	0.075 mg/m ³
57-55-6	Propylene glycol	30 mg/m ³
78-83-1	butanol	150 ppm
· PAC-2:	·	
123-86-4	n-butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
108-38-3	m-xylene	920 ppm
122-99-6	2-Phenoxyethanol	16 ppm
14808-60-7	Quartz (SiO2)	33 mg/m³
57-55-6	Propylene glycol	1,300 mg/m ³
78-83-1	butanol	1,300 ppm
· PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
110-43-0	heptan-2-one	4000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
108-38-3	<i>m-xylene</i>	2500* ppm
122-99-6	2-Phenoxyethanol	97 ppm
14808-60-7	Quartz (SiO2)	200 mg/m ³
57-55-6	Propylene glycol	7,900 mg/m ³
78-83-1	butanol	8000* ppm

7 Handling and storage

· Handling:

- Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

• Specific end use(s) No further relevant information available.

(Contd. on page 5)

.

Printing date 08/06/2018

0

Reviewed on 12/05/2017

Trade name: SHS50 BRIGHT RED MIXING TINT

(Contd. of page 4)

0	tional information about design of technical systems: No further data; see item 7.
Loni	rol parameters
	ponents with limit values that require monitoring at the workplace:
	following constituents are the only constituents of the product which have a PEL, TLV or othe
	nmended exposure limit.
At th	s time, the remaining constituent has no known exposure limits.
123-8	36-4 n-butyl acetate
PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
$\tau i V$	
ILV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm
110_	13-0 heptan-2-one
	•
	Long-term value: 465 mg/m ³ , 100 ppm
	Long-term value: 465 mg/m ³ , 100 ppm
	Long-term value: 233 mg/m ³ , 50 ppm
	11-4 ethylbenzene
	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm
	Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 87 mg/m³, 20 ppm BEI
Ingre	edients with biological limit values:
100-4	11-4 ethylbenzene
BEI	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	- Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: SHS50 BRIGHT RED MIXING TINT

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

 Information on basic physical and General Information 	chemical properties
 Appearance: Form: Color: Odor: Odor threshold: 	Liquid Red Characteristic Not determined.
· pH-value:	Not determined (pH N/A in solvent coatings)
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 124 ℃ (255.2 ℉)
· Flash point:	27 °C (80.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
· Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	1.064 g/cm³ (8.8791 lbs/gal) Not determined. Not determined. Not determined.
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
	(Contd. on page 2

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: SHS50 BRIGHT RED MIXING TINT

		(Contd. of page 6
 Viscosity: Dynamic: 	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	34.7 %	
VOC content:	34.69 %	
	375.6 g/l / 3.13 lb/gal	
Solids content:	64.8 %	
 Other information 	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- **Thermal decomposition** / **conditions to be avoided:** No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

DPP Red C.I Pigment 254

Oral LD50 5,000 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rat)

Primary irritant effect:

- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (Inter	national Agency for Research on Cancer)	
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
108-38-3	m-xylene	3
106-42-3		3
95-47-6	o-xylene	3
14808-60-7	Quartz (SiO2)	1
· NTP (Nation	nal Toxicology Program)	
14808-60-7	Quartz (SiO2)	K
		(Contd. on page 8)
		USA

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: SHS50 BRIGHT RED MIXING TINT

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, IMDG, IATA	UN1263	
· UN proper shipping name	Deint	
· DOT · IMDG, IATA	Paint PAINT	
· Transport hazard class(es)		
DOT		
RAMMARE LOUD		
Class	3 Flammable liquids	
		(Contd. on page

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: SHS50 BRIGHT RED MIXING TINT

	(Contd. of page
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
·Label	3
· Packing group · DOT, IMDG, IATA	III
 Environmental hazards: Marine pollutant: 	Νο
· Special precautions for user	Warning: Flammable liquids
 Danger code (Kemler): EMS Number: 	30
· Stowage Category	F-E, <u>S-E</u> A
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	<i>II of</i> <i>Not applicable.</i>
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
·IMDG	<i></i>
Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 35	55 (extremely hazardous substances):
None of the	e ingredients is listed.
· Section 31	13 (Specific toxic chemical listings):
1330-20-7	xylene
100-41-4	ethylbenzene
108-38-3	m-xylene
106-42-3	p-xylene
95-47-6	o-xylene
122-99-6	2-Phenoxyethanol
· TSCA (To)	xic Substances Control Act):
All ingredie	ents are listed.
	(Contd. on page 10)

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: SHS50 BRIGHT RED MIXING TINT

(Contd. of page 9)

I D

1

1

1

 Proposition 	n 65
	known to cause cancer:
100-41-4	ethylbenzene

14808-60-7 Quartz (SiO2)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene 100-41-4 ethylbenzene

108-38-3 m-xylene

106-42-3 p-xylene

95-47-6 o-xylene

· TLV (Threshold Limit Value established by ACGIH)

1330-20-7		A4
	, ,	A3
	,	A4
106-42-3		A4
	,	A4
14808-60-7	Quartz (SiO2)	A2
· NIOSH-Ca (National Institute for Occupational Safety and Health)		

14808-60-7 Quartz (SiO2)

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



· Signal word Warning

Hazard-determining components of labeling: n-butyl acetate
Hazard statements
Flammable liquid and vapor.
Suspected of causing cancer.
May cause drowsiness or dizziness.
Precautionary statements
Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment.

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: SHS50 BRIGHT RED MIXING TINT

(Contd. of page 10)
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
• •
16 Other information
This information is based on our present knowledge. However, this shall not constitute a guarantee for
any specific product features and shall not establish a legally valid contractual relationship.
 Department issuing SDS: Environment protection department.
Contact: Product Safety Dept.
· Date of preparation / last revision 08/06/2018 / 2
· Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the
International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety
NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 3: Flammable liquids – Category 3
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
· * Data compared to the previous version altered.