

Page 1/9

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.04.2020 Version number 5 Revision: 03.04.2020

### 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: L12.4.K1 Flat DTM Binder
- · Article number: L12.4.K1
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
  Lusid Technologies
  4725 S Camp Kearns Road
  Kearns, UT 84118
  USA

www.lusidtechnologies.com

- · Further information obtainable from: Product safety department
- · Emergency telephone number:

Emergency US - 1-800-535-5053 Outside US - +1-352-323-3500 InfoTrac Contract 89244

#### 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.04.2020 Version number 5 Revision: 03.04.2020

Trade name: L12.4.K1 Flat DTM Binder

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:
- n-butyl acetate
- · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate. May produce an allergic reaction.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 98-56-6 EINECS: 202-681-1 Reg.nr.: 01-2119857280-40	4-chloro-alpha,alpha,alpha-trifluorotoluene      Flam. Liq. 3, H226;    Skin Irrit. 2, H315; Eye Irrit. 2, H319	25-50%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 RTECS: AF 7350000 Reg.nr.: 01-2119485493-29	n-butyl acetate <b>③</b> Flam. Liq. 3, H226; <b>①</b> STOT SE 3, H336	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49	acetone  State   State    acetone    Flam. Liq. 2, H225; State    Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%

(Contd. on page 3)

Printing date 03.04.2020 Version number 5 Revision: 03.04.2020

Trade name: L12.4.K1 Flat DTM Binder

CAS: 110-43-0	heptan-2-one	2.5-10%
EINECS: 203-767-1 Index number: 606-024-00-3 Reg.nr.: 01-2119902391-49-0000	<ul> <li>Flam. Liq. 3, H226;</li> <li>Acute Tox. 4, H302; Acute Tox. 4, H332</li> </ul>	
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate)  Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≤2.5%
CAS: 41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate ♦ Skin Sens. 1, H317	≤2.5%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

Printing date 03.04.2020 Version number 5 Revision: 03.04.2020

Trade name: L12.4.K1 Flat DTM Binder

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

#### 123-86-4 n-butyl acetate

IOELV Short-term value: 723 mg/m³, 150 ppm

Long-term value: 241 mg/m³, 50 ppm

67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

110-43-0 heptan-2-one

IOELV Short-term value: 475 mg/m<sup>3</sup>, 100 ppm

Long-term value: 238 mg/m³, 50 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

(Contd. of page 4)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.04.2020 Version number 5 Revision: 03.04.2020

Trade name: L12.4.K1 Flat DTM Binder

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Colour: Whitish

Odour: Product specific
 Odour threshold: Not determined.
 pH-value: Not determined.

Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 55.8-56.6 °C

· Flash point: <-18 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 370 °C

· **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

**Lower:** 1.2 Vol %

(Contd. on page 6)

Printing date 03.04.2020 Version number 5 Revision: 03.04.2020

Trade name: L12.4.K1 Flat DTM Binder

		(Contd. of page
Upper:	7.5 Vol %	
· Vapour pressure at 20 °C:	10.7 hPa	
· Density at 20 °C:	1.1523 g/cm³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Fully miscible.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	51.5 %	
VÕC (EC)	91.52 %	
Solids content:	7.4 %	
· Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

#### 7779-90-0 trizinc bis(orthophosphate)

Oral LD50 >5,000 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 03.04.2020 Version number 5 Revision: 03.04.2020

Trade name: L12.4.K1 Flat DTM Binder

(Contd. of page 6)

- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information		
· UN-Number · ADR, IMDG, IATA	UN1300	
· UN proper shipping name · ADR · IMDG, IATA	1300 TURPENTINE SUBSTITUTE TURPENTINE SUBSTITUTE	

(Contd. on page 8)

Printing date 03.04.2020 Version number 5 Revision: 03.04.2020

Trade name: L12.4.K1 Flat DTM Binder

(Contd. of page 7)

· Transport hazard class(es)

· ADR, IMDG, IATA



3 Flammable liquids. · Class

·Label

· Packing group

II· ADR, IMDG, IATA

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 33 F-E.S-E · EMS Number: · Stowage Category В

· Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: E2

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· Transport category D/E

· Tunnel restriction code

· IMDG

1L · Limited quantities (LQ)

Code: E2 · Excepted quantities (EQ)

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1300 TURPENTINE SUBSTITUTE, 3, II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).

(Contd. on page 9)

Printing date 03.04.2020 Version number 5 Revision: 03.04.2020

Trade name: L12.4.K1 Flat DTM Binder

(Contd. of page 8)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### · Department issuing SDS: Environment protection department.

· Contact: Mr. Roberts

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

EU